




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : B65D 19/00		A1	(11) International Publication Number: WO 00/01588
			(43) International Publication Date: 13 January 2000 (13.01.00)
(21) International Application Number: PCT/US99/14399 (22) International Filing Date: 25 June 1999 (25.06.99) (30) Priority Data: 09/108,532 1 July 1998 (01.07.98) US 09/330,150 11 June 1999 (11.06.99) US (71) Applicant: REHRIG PACIFIC COMPANY [US/US]; 4010 East 26th Street, Los Angeles, CA 90023 (US). (72) Inventor: APPS, William, P.; 225 Lake Height Drive, Alpharetta, GA 30202 (US). (74) Agents: DIAMOND, Konstantine, J. et al.; Brooks & Kushman, 22nd floor, 1000 Town Center, Southfield, MI 48075 (US).		(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i>	

(54) Title: PALLET ASSEMBLY



(57) Abstract

A pallet assembly (10) includes a top deck (14) formed of plastic which has a first opposing surface having a plurality of first flanged portions (34) projecting downwardly therefrom. The top deck (14) has a substantially planar upper surface upon which a plurality of objects are capable of resting. The pallet assembly (10) also includes a bottom deck (12) which is also formed of plastic and a second opposing surface with a plurality of second flanged portions (36) projecting therefrom in an upward direction. The plurality of second flanged portions correspond to and securely mate with the plurality of flanged portions to define a plurality of columns (20) between the top and bottom decks, the columns having a box beam cross section for providing strength to the pallet assembly. The top deck (14) includes a top member (30) and a mid-top member (40), and the bottom deck (12) includes a bottom member (42) and a mid-bottom member (44).

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LJ	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

PALLET ASSEMBLY

TECHNICAL FIELD

5 This invention relates to a plastic pallet assembly for storing or transporting goods.

BACKGROUND ART

10 Pallets used in industry today are most commonly formed of wood slats and stringers or blocks which are nailed together. While such pallets are functional, they have many disadvantages. First, wood pallets are relatively heavy. Second, wood is not easily cleaned because it absorbs water and other liquids which damage and warp the wood. For these same reasons, the use of wood pallets outside or in wet environments is also limited. Wood pallets are often not consistently dimensioned due to size variations in the wood slats and shrinkage of wood over
15 time, thus preventing such pallets from being stacked or stored in a stable or consistent manner. Also, inconsistent dimensions make automation of these pallets more difficult. Further, the nails used to fasten wood pallets together may cause damage to goods which are stored and transported on the pallet, or wood splinter may result after time. Moreover, once wood pallets are damaged, they have little
20 or no residual value and also necessitate disposal fees.

Replacing wood pallets with plastic pallets has been a goal for many years. The advantages of plastic pallets are many as compared to wood, including greater durability, lighter weight, more consistent dimensions, improved cleanliness, water resistance, higher residual value for recycling, and no nails which may damage
25 products being supported thereon. While many plastic pallets have been attempted, the designs that are able to approximate the strength of wood, to date, have been cost prohibitive and may not have the requisite strength properties. For example, plastic

pallets having a solid section, while having favorable stiffness and deflection properties, are heavy and utilize a relatively large quantity of material in their formation. Wood is five to eight times stiffer than a typical plastic used to make pallets. Plastic pallets must either use much more material, be taller, or have
5 reinforcements such as steel rods or glass fillers to compensate for this difference. While conventional plastic pallets have ribbed supports to decrease their weight, they often lack the desired stiffness and low creep properties of the solid pallet, and in order to improve these properties, the height of the pallet must be increased, or reinforcements must be added to the plastic such as steel or other composite
10 reinforcements. Of course, these additions to the plastic cause an increase in material density leading to an even heavier pallet. Further, engineering resins are very expensive resulting in a more expensive pallet.

Another hurdle to overcome with plastic is the cost. Plastic pallets are more expensive than wood by three to five times. This cost can be offset by the
15 number of trips or shipments that can be achieved with plastic versus wood pallets. Another major hurdle is the stiffness of plastic pallets. Racking loaded pallets in warehouses for upwards of 30 days may be common, and the combination of low tensile strength and creep may limit the use of plastic in this manner.

There are three conventional methods of overcoming these
20 weaknesses. The first is to add reinforcement such as steel or a composite to the pallet. This generally adds significant cost and weight and complicates recycling of the pallet. The second is to make the pallet taller. This generally limits the height of a product which is to be stacked on the pallet, as well as the number of pallets that may be stored in a given area. The third is to use reinforced or engineered resins.
25 Again, this adds significant cost and weight. All three obviously limit the acceptance of plastic pallets.

U.S. Patent No. 3,580,190 provides a partial solution to the stiffness problem by attaching top and bottom sheets 22,24 to the structural network 23, as shown in Figure 1 thereof. However, this solution does not resolve the bending
30 stiffness problem because large lateral and longitudinal unsupported areas still exist,

such as in areas 26, 37, 38, 49 and 50. In other words, this design merely further stiffens the support column areas 67, 68, 69, 97, 98, 99, 28, 30, 32, which already provide substantial stiffness merely as a result of their height. The weakness of this design is apparent in column 6, lines 60-71, where the reference recommends the use of a material having a flexural modulus (or Young's modulus) greater than about 200,000 psi. Such a high modulus material is apparently required because the structure described does not provide significant resistance to deflection along the length and width of the pallet. High modulus materials add substantial cost to the pallet.

Moreover, pallets typically require large openings for receipt of pallet jacks. Because of these large openings, the pallet structure is typically thin and weak and has poor deflection stiffness. Because pallets are exposed to significant abuse, any solution to the stiffness problem must not adversely affect the impact strength of the pallet.

Consequently, an improved pallet is desired which should be reasonably inexpensive, lightweight and sturdy. The improved pallet should also have improved stiffness and creep properties. The pallet should also be able to withstand various environmental conditions to which it may be exposed, particularly moisture. The improved pallet should also be easy to store, have a size compatible with a standard wood pallet, and be reusable. Also, a need exists for improving the stiffness of plastic pallets configured to receive a pallet jack, without reducing impact strength of the pallet. The improved pallet design should also apply to components used in association with pallets.

DISCLOSURE OF INVENTION

It is a principal object according to the present invention to provide an improved pallet assembly which is relatively lightweight, inexpensive to manufacture and assemble, and consistently dimensioned.

5 It is another object according to the present invention to provide an improved pallet assembly which has desirable strength, stiffness, creep, and deflection properties.

 It is another object according to the present invention to provide an improved pallet assembly which is able to withstand varied environmental conditions,
10 particularly moisture, with little damage or wear and is readily reusable.

 It is yet another object according to the present invention to provide an improved pallet assembly which may be stored, racked or stacked in a stable manner.

 Another object of the present invention is to provide a method of
15 structurally reinforcing a plastic pallet configured to receive a pallet jack, in a manner which improves stiffness without loss of impact strength.

 It is yet another object to provide a highly stiff pallet without the use of the reinforcements or engineered resins which increase the cost and weight of the pallet, i.e., to provide an inherently stiff pallet design.

20 Further, it is another object according to the present invention to provide an improved design for components used in association with pallets, such as a pallet top frame.

 In carrying out these and other objects and goals according to the present invention, a pallet assembly is provided which includes a top deck formed
25 of plastic which has a first opposing surface having a plurality of first flanged

portions projecting downwardly therefrom. The pallet assembly top deck portion has a substantially planar upper surface upon which a plurality of objects may be rested. The pallet assembly also includes a bottom deck portion which is also formed of plastic and has a second opposing surface with a plurality of second flanged portions projecting therefrom in an upward direction. In this assembly, the pluralities of second flanged portions correspond to and securely mate with the plurality of first flanged portions to define a plurality of columns between the top deck and bottom deck portions, said top and bottom deck portions and said columns having a box beam cross-section for providing strength to the pallet assembly.

The overall box beam pallet design according to the present invention also has desirable improved properties, such as increased stiffness versus weight, over other standard beam section designs having equivalent surface areas, sizes, and weights, such as a T-rib beam, or an inverted-U (multiple ribbed) design, and has properties equivalent to that of the I-beam section.

In a preferred assembly, the top deck portion includes a top member and a mid-top member which have corresponding mating flanged surfaces which are securely mated to each other. In this preferred assembly, the mid-top member has the first opposing surface opposite the corresponding mating flanged surfaces. In still another preferred assembly, the bottom deck portion includes a bottom member and a mid-bottom member each having corresponding mating flanged surfaces which are securely mated to each other. In this preferred assembly, the mid-bottom member has the second opposing surface opposite its corresponding mating flange surfaces.

More particularly, the first or top member includes a substantially flat top surface with ribs protruding in a downward direction. The second or mid-top member has a substantially flat bottom surface with ribs extending in an upward direction and partial support columns extending down from this surface. The ribs on both these parts are aligned so they can be welded together by plasticizing their mating surfaces preferably via a hot-plate welding operation to form a box beam top deck. The third or mid-bottom member has a substantially flat upper surface with

ribs extending down and partial columns extending up. The fourth or bottom member has a substantially flat bottom surface with ribs extending up. Again, the ribs on both parts are aligned so they can be welded together in a second hot plate welding operation to form a box beam bottom deck. Lastly, the box beam top deck and box beam bottom deck are welded together at the columns that also align, resulting in a pallet where every section is a box beam. In the preferred embodiment, each boxed section has a perforated top and bottom to allow for cleaning and drainage. These perforations may easily be eliminated to create true boxed sections.

10 In a second embodiment according to the present invention, there is provided a plastic pallet assembly which includes a first pallet portion which is formed of plastic and has a first opposed surface having a plurality of first spacer portions projecting downwardly therefrom which define a first matching surface. This second embodiment also includes a second pallet portion which is also formed of plastic and has a second opposed surface having a plurality of second spacer portions projecting upwardly therefrom which define a second matching surface. The plurality of first and second matching surfaces are then heated to a plasticized state, compressed together, and subsequently cooled in order to define a plurality of columns for spacing apart the first pallet portion and the second pallet portion, each column, first and second pallet portions each having a box beam cross-section for providing strength to the pallet assembly. This method is preferably performed via hot plate welding. In a preferred version of this second embodiment, the first pallet portion includes a first outer member and a first inner member having opposing surfaces which are securely attached to each other by heating them to a plasticized state, compressing them together, and cooling them. As in the first embodiment, the first outer member has a substantially planar first outer surface for supporting and transporting one or more objects thereupon.

Further, the second pallet portion may include a second outer member and a second inner member which have opposing surfaces securely mounted to each other by the process of heating the opposing surfaces to a plasticized state, compressing them together, and cooling them.

In a third embodiment according to the present invention, a plastic pallet assembly includes a first pallet portion which is formed of plastic and includes a top member and a top intermediate member (mid-top member). Each of these members has a first pair of substantially planar surfaces spaced apart from the other and each further has a first pair of mating surfaces which are heat welded together in order to integrally define the first pallet portion. The third embodiment of the plastic pallet assembly also includes a second pallet portion which is formed of plastic and includes a bottom member and a bottom intermediate member (mid-bottom member), each having a second pair of substantially planar surfaces spaced apart from the other and each further having a second pair of mating surfaces which are heat welded together in order to integrally define the second pallet portion. The first intermediate member of the first pallet portion and the second intermediate member of the second pallet portion each has corresponding opposed mating edges which are heat welded together in order to integrally define the pallet assembly.

A fourth embodiment of the pallet assembly according to the present invention is formed substantially of plastic. The fourth embodiment includes a first outer member and a first intermediate member which are spaced apart from each other by a first pair of opposed mating surfaces extending therebetween. The opposed mating surfaces are integrally mounted to each other in order to define a first pallet portion. The fourth embodiment also includes a second outer member and a second intermediate member which are spaced apart from each other by a second pair of opposed mating surfaces extending therebetween. The second pair of opposed mating surfaces is integrally mounted to each other in order to define a second pallet portion. The second intermediate member is oriented adjacent the first intermediate member. The first intermediate member and the second intermediate member have corresponding mounting edges projecting therefrom which are integrally mounted to each other in order to integrally define the pallet assembly. In this embodiment, the first outer member includes a lower surface with edges projecting therefrom which defines a one of the first pair of opposed mating surfaces, and the first intermediate member has an upper surface with corresponding edges projecting therefrom which defines an other of the first pair of opposed mating surfaces. The second outer member includes an upper surface with edges projecting

therefrom which defines a one of the second pair of opposed mating surfaces, and the second intermediate member has a lower surface with corresponding edges projecting therefrom which defines an other of the second pair of opposed mating surfaces.

5 A fifth embodiment of the portable pallet assembly according to the present invention is for storing and transporting objects thereon and includes a first member which has a substantially planar first upper surface upon which the objects are placed, and also includes a first lower surface. This fifth embodiment also includes a second member which has a second upper surface and a second lower
10 surface, where the second upper surface is securely mounted to the first lower surface to form a plurality of box beam cross-sections. The fifth embodiment further includes a third member which has a third upper surface and a third lower surface. The third upper surface and the second lower surface have corresponding flanged surfaces which are securely mounted to each other to in order to form a plurality of
15 columns having box beam cross-sections defined thereby. This embodiment also includes a fourth member which has a fourth upper surface for mating with the third lower surface and also has a substantially planar fourth lower surface. The fourth upper surface is securely mounted to the third lower surface to form a plurality of box beam sections.

20 In a preferred version of this fifth embodiment, the second upper surface and first lower surface are each securely mounted to each other by introducing heat therebetween, plasticizing each surface, compressing the surfaces together, and allowing them to cool. In another preferred version, the fourth upper surface and third lower surface are securely mounted to each other by introducing
25 heat therebetween, plasticizing each surface, compressing the surfaces together, and allowing them to cool.

 Also disclosed according to the teachings of the present invention is a top frame for a pallet. A top frame is typically used in connection with the mass shipping of objects, such as empty bottles. The top frame is used to help stabilize
30 the shipment of objects at the upper end in conjunction with a pallet at the lower end.

In keeping with the teachings of the present invention, a method for forming a pallet and a top frame for a pallet includes providing first and second pallet portions, each having corresponding mating flanged surfaces. The method also includes introducing heat to the corresponding mating flanged surfaces to melt the mating flanged surfaces in order to thereby form plasticized surfaces. The plasticized surfaces may then be pressed together, and then cooled to form a welded joint therebetween defining a plurality of box sections by the mating flanged surfaces. In this method, the step of providing a first and second pallet portions includes mounting and aligning them in a holding fixture. The step of introducing heat may include introducing a heated platen therebetween. Also, the method may also include the steps of retracting the heated platen from between the corresponding mating flanged surfaces prior to pressing them together and also opening the holding fixture and removing the welded pallet assembly at or near the end of the forming operation. The method may further include heating the mating flanged surfaces under pressure by contacting the heated platen to the mating flanged surfaces for melting the same.

In another method embodiment, more specifically, the present invention provides a method of reinforcing a plastic pallet having a thin top deck portion, a plurality of support columns extending from the top deck portion and a plurality of support rails connected to the support columns to form a thin bottom deck portion, wherein the support rails each include a sheet portion with a plurality of vertical ribs extending therefrom. The method includes the step of welding a plurality of plastic sheets to the vertical ribs between the support columns to form a plurality of substantially rectangular hollow vertical cross-sections along the length of the support rails for improved stiffness. It is contemplated that the substantially rectangular hollow vertical cross-sectional areas may be filled with a secondary material, such as structural foam for improved structural integrity.

The present invention also provides for partial reinforcement of a plastic pallet by affixing sheet strips along relatively weak structural portions of the pallet to form a plurality of substantially rectangular hollow vertical cross-sections

along the length of the relatively weak structural portions for improved stiffness without loss of impact strength.

5 The above objects and other objects, features, and advantages of the present invention are readily apparent from the following detailed description of the best modes for carrying out the invention when taken in connection with the accompanying drawings wherein like reference numerals correspond to like components.

BRIEF DESCRIPTION OF DRAWINGS

10 FIGURE 1 is a top perspective view of a pallet assembly according to the present invention;

FIGURE 2 is a bottom perspective view of the pallet assembly;

FIGURE 3 is an exploded top perspective view of the pallet assembly, showing the top deck and bottom deck;

15 FIGURE 4 is a bottom perspective view of the pallet assembly, showing the bottom deck and the top deck;

FIGURE 5 is another exploded top perspective view of the pallet assembly showing the upper member, the first intermediate (mid-top) member, the second intermediate (mid-bottom) member and the bottom member of the pallet assembly;

20 FIGURE 6 is a bottom perspective view of a pallet assembly, showing the bottom member, the second intermediate member, the first intermediate member and the upper member of the pallet assembly;

FIGURE 7 is a top perspective view of a quarter section of the pallet assembly according to the present invention;

FIGURE 8 is a bottom perspective view of the quarter section of the pallet assembly;

FIGURE 9 is an exploded top perspective view of the quarter section of the pallet assembly, showing the top deck and bottom deck;

5 FIGURE 10 is a bottom perspective view of the quarter section of the pallet assembly, showing the bottom deck and the top deck;

10 FIGURE 11 is another exploded top perspective view of the quarter section of the pallet assembly showing the upper member, the first intermediate member, the second intermediate member and the bottom member of the pallet assembly;

FIGURE 12 is a bottom perspective view of the quarter section of the pallet assembly, showing the bottom member, the second intermediate member, the first intermediate member and the upper member of the pallet assembly;

15 FIGURE 13 is a sectional view of the pallet assembly taken along line 13-13 of Figure 7;

FIGURE 14 is an exploded side elevational sectional view as shown in Figure 7, with the top member, mid top member, mid bottom member and bottom member shown separated;

20 FIGURE 15 is another exploded side elevational sectional view of Figure 7, showing the top deck and bottom deck separated;

FIGURES 16a-f illustrate the method according to the present invention of forming and assembling the pallet assembly;

FIGURE 17 is a perspective view of a top frame assembly according to the present invention;

FIGURE 18 is a side view of the top frame assembly in operation with the pallet assembly and having objects to be transported disposed therebetween;

FIGURE 19 is a top plan view of the top frame assembly;

FIGURE 20 is a front elevational view of the top frame assembly;

5 FIGURE 21 is a side elevational view of the top frame assembly;

FIGURE 22 is a sectional view taken along the line 22-22 of Figure 19;

FIGURE 23 is a sectional view taken along the line 23-23 of Figure 19;

10 FIGURE 24 is a bottom plan view of the first top frame member, the top plan view of the second top frame member being substantially similar thereto;

FIGURE 25 illustrates an exploded perspective view of the first and second top frame members according to the present invention;

15 FIGURE 26 illustrates a partially separated first top frame member and second top frame member;

FIGURE 27 is a cross-sectional view taken along a line parallel to the longitudinal center line of the top frame, at line 27-27 in Figure 19;

FIGURE 28a illustrates a perspective view of a second embodiment of a top frame according to the present invention;

20 FIGURE 28b illustrates a partially exploded perspective view of the second embodiment of the top frame;

FIGURE 28c illustrates an exploded perspective view of the second embodiment of the top frame;

FIGURE 29 shows a perspective view of another embodiment of a plastic pallet in accordance with the present invention;

5 FIGURE 30 shows a bottom exploded perspective view of the pallet of Figure 29;

FIGURE 31 shows a top exploded perspective view of the pallet of Figure 29;

10 FIGURE 32 shows a cutaway perspective sectional view of a pallet in accordance with an alternative embodiment of the invention;

FIGURE 33 shows a top exploded perspective view of a pallet in accordance with a second alternative embodiment of the invention; and

FIGURE 34 shows a bottom exploded perspective view of the pallet of Figure 33.

15 **BEST MODE FOR CARRYING OUT THE INVENTION**

Figure 1 of the drawings shows a top perspective view of a pallet assembly 10 according to the present invention. Pallet assembly 10 is formed of a thermoplastic or other polymeric material and is preferably, but not necessarily, formed of injection molded components. As illustrated in Figure 1, pallet assembly 10 includes a top deck 12 and a bottom deck 14 which are spaced apart from each other. Pallet assembly 10 also includes a plurality of columns which extend between the spaced apart top deck 12 and bottom deck 14. The pluralities of columns include corner column portions 16, side column portions 18, and end column portions 19

20

shown extending between top deck 12 and bottom deck 14. The columns are shown having smooth, rounded outer surfaces in order to prevent damage from fork lift trucks and the like. However, any suitable contour may be used depending on the application. In addition to separating top deck 12 and bottom deck 14, column
5 portions 16, 18, 19 and 32 serve to bear and distribute the load of the objects (for example, the bottles shown in Figure 18) placed upon top deck 12, and more particularly objects intended to be supported on a top surface 26 of top deck 12.

In one embodiment, top surface 26 is preferably non-skid in order to prevent objects from sliding off during transport. Again, however, any suitable
10 surface texture or geometry may be used depending on the application without departing from the spirit of the invention. As discussed further herein, Figure 1 illustrates that top deck 12 and bottom deck 14 are joined together at a parting line 20. In a preferred embodiment, top deck 12 and bottom deck 14 also have a plurality of apertures 22 and 24, respectively, formed therethrough in order to
15 decrease the overall weight of pallet assembly 10, as well as provide for a method of draining water and other liquid/debris from pallet assembly 10 so that the liquid/debris is not accumulated thereon. Thus, such apertures are particularly helpful when washing the pallet. Apertures 22, 24 may be any suitable shape, dimension, and density and disposed in a variety of combinations ranging from
20 densely perforated to no perforations depending on the desired application.

Of course, top deck 12 and bottom deck 14 may also have continuous surfaces without apertures 22 and 24. As previously mentioned, top deck 12 includes a substantially flat planar upper surface 26 (first outer surface) upon which objects and goods may be placed for transport and storage. Pallet assembly 10 also
25 includes a plurality of openings 25 for receiving the forks of a fork lift therethrough (best shown in Figure 13.)

Figure 2 of the drawings illustrates a bottom perspective view of pallet assembly 10. As shown therein, bottom deck 14 includes a substantially flat planar
30 bottom surface 28 for secure placement upon a ground or other resting surface, or also for stable orientation on a similarly designed pallet for stacking purposes. Note

that bottom deck 14 also has four relatively larger openings 30 situated therein for accommodating pallet jacks. Although shown as substantially rectangular in shape, openings 30 may be any suitable shape and dimension limited only by the desired application. In addition to corner column portions 16, side column portions 18, and end column portions 19, a central column portion 32 is provided in the central area of the pallet assembly between top deck 12 and bottom deck 14, and like its counterparts also serves to bear and distribute the loads placed on top deck 12.

Figure 3 is a semi-exploded view of pallet assembly 10 showing top deck 12 and bottom deck 14 spaced apart from each other and separated at parting line 20. Parting line 20 is a plane defined by the mating top and bottom column portion surfaces 34 and 36, respectively. It is the mating column portion 34 and 36, and more particularly mating column surfaces 35 and 37, which are plasticized and joined together in order to assemble pallet assembly 10 according to the present invention, as discussed further herein. As can also be seen by reference to Figure 3, column portions 16, 18, 19 and 32 are each designed as having a closed section or box section for achieving the objects and goals set forth herein. Figure 4 illustrates a semi-exploded bottom perspective view of pallet assembly 10 showing bottom deck 14 and top deck 12 spaced apart at parting line 20 and again showing from a different angle mating column portions 34 and 36.

Figure 5 is yet another exploded top perspective view of pallet assembly 10. More specifically, Figure 5 illustrates a fully exploded top perspective view of pallet assembly 10 wherein top deck 12 and bottom deck 14 are each shown as separated into the preferable four principal pallet assembly 10 components. As shown therein, top deck 12 has a top member 38 (also referred to as first member or first outer member) and a mid-top member 40 (also referred to as first (or top) intermediate member or first inner member.) Further, bottom deck 14 has a bottom member 42 (also referred to as second member or second outer member) and a mid-bottom member 44 (also referred to as second (or bottom) intermediate member 44 or second inner member.) Again, as more fully disclosed later herein, it is contemplated that top member 38 and mid-top member 40 are coupled together to form top deck 12 by plasticizing mating surfaces via the same or similar processes

used to join top deck 12 to bottom deck 14. Similarly, it is contemplated that bottom member 42 and mid-bottom member 44 are also joined together to form bottom deck 14 via a similar process.

As further illustrated in Figure 5, top member 38 includes upper surface 26 upon which objects are placed to be transported or stored. Hence, it is the surface of top member 38 which is opposite upper surface 26 -- referred to as top member lower surface 46 (best shown in the bottom perspective exploded view of Figure 6) -- which is adjoined to a mating planar upper surface 48 of mid-top member 40 via the disclosed plasticizing process in order to form top deck 12. As previously discussed, bottom member 42 includes bottom surface 28 for resting on floors and other resting surfaces. The surface of bottom member 42 which is opposite bottom surface 28 -- referred to as bottom member upper 50 -- is attached to a corresponding mating lower planar surface 51 of mid-bottom member 44.

Figure 6 is a fully-exploded bottom perspective view of pallet assembly 10 illustrating its four components, as previously discussed in association with Figure 5. These features are all shown in Figure 14.

Referring now to Figures 7, 12, and 13, a quarter section 55 of pallet assembly 10 particularly illustrates the cross-sectional box-beam shape disclosed herein according to the present invention. As illustrated in Figures 7, 12 and 13, a representative box beam section is shown for top deck 12, the box beam section defined by upper surface 26, mid-top member planar surface 41, and mating flange pairs 62-72 and 63-73 which are each fastened together. Another representative box beam section is shown defined by surfaces 26 and 41 and mating flanges pairs 63-73 and 64-74 which are each fastened together.

Figures 13 illustrates bottom deck 14 having a representative box beam section which is defined by bottom surface 28, mid-bottom surface 45, and mating flange pairs 82-92 and 83-93 which are also each fastened together, and another representative box beam section further defined by surfaces 28 and 45, and mating flange pairs which are fastened together, these being pairs 83-93 and 84-94.

In keeping with the invention, the preferred fastening means is via hot plate welding. However, any suitable fastener may of course be used depending on the application, including without limitation infrared radiation, epoxy, etc.

Also, note that box beam sections are included with respect to the column portions of pallet assembly 10, which include representative central column portion 32, side column portion 18 and end column portion 19. For example, the cross-section through side column portion 18 as shown in Figure 7 illustrates the presence of a box beam section, shown as four wall portions 18a, 18b, 18c and 18d, defining therein a rectangular aperture 27 therethrough. Also, with further reference to Figure 3, note that box beam sections are disclosed throughout the column portions, for examples defined by wall members 2, 3, 4, and 5 of column 20. Under equivalent applied loads, the box beam design disclosed herein has improved deflection and strength properties over a conventional ribbed pallet design having a ribbed support structure (such as the T-rib or the inverted-U rib designs). For example, to accommodate for the lower stiffness, the T-rib would require approximately 17% increase in height compared to the box beam section.

With particular reference to the exploded perspective views of pallet quarter section 55 shown in Figures 11 and 12, note that mating flanges extend across top deck 12 and bottom deck 14, both longitudinally (for example, flanges 62, 72, 82, 92) and transversely (for example, flanges 162, 172, 182, 192) in a perpendicular orientation and pattern, in order define, when welded together, the plurality of box sections described heretofore. As shown in the exploded views of Figures 5, 6, 11 and 12, such box sections extend in a continuous manner across top deck 12 and bottom deck 14. More particularly with reference to Figures 11-12, note that the box sections of top deck 12 are relatively smaller box beam sections in the central and outer areas (for example, the box beam section defined by mating areas 21 and 21'), while they are relatively larger in the central portion of each of the four quarter sections, such as quarter section 55 (for example the box beam section defined by areas 23 and 23'.)

With continued reference to Figures 11-12, it is noted that this box beam section layout is similar for bottom deck 14, wherein it is noted that the box beam sections are relatively smaller and concentrated closer together in between openings 30, in order to provide greater strength to these areas, as is noted by the
5 box beam section formed of welded mating areas 43 and 43'. On the other hand, larger box beam sections of bottom deck 14 are provided toward the outer edges, such as the section formed by welding mating areas 33 and 33'.

The box beam design for top deck 12, bottom deck 14, and the column portions disclosed herein also achieve properties similar to a solid pallet
10 design, but of course, by definition the box beam uses less material and is therefore less expensive and lighter than its solid counterpart. Further, a conventional ribbed pallet design typically does not achieve the deflection or stiffness requirements of the box beam design according to the present invention, and would also require a reinforced or engineered resin and would need to be relatively taller to achieve the
15 relatively high stiffness. The conventional design also would not meet the desirable properties of the design according to the present invention, given equivalent part weights, loads, and flexural moduli implemented in design comparisons.

With reference now to Figure 8 of the drawings, shown therein is a bottom perspective view of quarter section 55 shown in Figure 7. Figure 8 is similar
20 to the full pallet bottom perspective view of Figure 2, but as mentioned is a quarter section 55 of full pallet assembly 10.

Figure 9 shows the top perspective view of quarter section 55 from Figure 7 exploded into top deck 12 and bottom deck 14. This quarter section view is similar to the corresponding bottom perspective view of the full pallet illustrated
25 and disclosed previously in association with Figure 3. Likewise, Figure 10 is an exploded view of a bottom perspective view of quarter section 55 shown in Figure 8 exploded into bottom deck 14 and top deck 12. This view is similar to the corresponding perspective view of full pallet bottom of Figure 4.

Figure 11 is yet another fully exploded view of the top perspective view of quarter section 55 shown in Figure 7, showing the various members included in pallet assembly 10, which are top member 38, mid-top member 40, bottom member 42 and mid-bottom member 44. This view is similar to the full pallet exploded perspective view of Figure 5. Similarly, Figure 12 is another fully exploded view of the bottom perspective view of quarter section 55 of Figure 8 showing the various components included in the pallet assembly 10. Similar to the full pallet fully exploded perspective view of Figure 6.

Figure 13 is a cross-sectional view of quarter section 55 of pallet assembly 10 shown in Figures 7-12. More particularly, Figure 13 is an elevational view of pallet quarter section 55 taken along centerline line 13-13 of Figure 7. While the various members 38, 40, 42 and 44, in a preferred embodiment, are formed of a like material, for ease of reference, these members are illustrated as having different crosshatching in order to easily demarcate between the walls of the various members as shown in this cross-section. As in Figure 7, the closed or box-beam cross-section of the column portions is apparent from Figure 13, represented by side column portion 18.

Particularly, Figures 13-15 illustrates the mating portions of pallet assembly 10 which are plasticized and joined according to the present invention, and particularly assembled via the hot plate welding process as discussed further herein. Note that in addition to parting line 20 between top deck 12 and bottom deck 14, there are two additional parting lines shown, those being an upper parting line 52 defined by a plane between top member 38 and mid-top member 40, and a bottom parting line 54 defined by a plane between bottom member 42 and mid-bottom member 44. Parting lines define the respective weld planes according to the present invention.

According to the present invention, each of the adjacent and adjoining members of pallet-assembly 10 are preferably joined together at the planar surfaces or portions which define the corresponding parting lines 20, 52 and 54. With reference to Figure 14, it is noted that parting line 20 is defined by mating planar

surfaces 35 and 37; upper parting line 52 is defined by mating planar surfaces 69 and 79; and lower parting line 54 is defined by mating planar surfaces 50 and 51. As best illustrated in the sectional view of Figure 15 shown having top deck 12 and bottom deck 14 spaced apart, it is shown that the corresponding mating ribs 100-105 of top deck 12 and ribs 110-115 of bottom deck 14 are plasticized and welded together, preferably via the hot plate welding process. Similarly, as shown in the full exploded view of Figure 14, the members forming top deck 12 and bottom deck 14 are similarly welded together at their corresponding mating ribs. Therefore, with reference again to Figure 14, ribs 60-67 of top member 38 and ribs 70-77 of mid-top member 40 are melted or plasticized, preferably during the hot plate welding process, and welded to their mating corresponding ribs. Therefore, the flanges or ribs extending downward from top member 38 (flanges 60, 61, 62, 63, 64, 65, 66 and 67) are heated to a melted state and joined, respectively, with mating flanges 70, 71, 72, 73, 74, 75, 76 and 77, respectively, which extend upward from mid-top member 40.

Similarly, the components forming bottom deck 14 are joined in the same fashion, so that integrally molded flanges 80, 81, 82, 83, 84, 85, 86, 87 (80-87) which extend upward from bottom member 42 are heated to a plasticized state and pressed together with respective opposed mating integrally molded flanges 90, 91, 92, 93, 94, 95, 96, 97 (90-97), respectively, extending downward from mid-bottom member 44. After top deck 12 and bottom deck 14 have each been joined or welded, Figure 15 shows that top deck 14 is then welded to bottom deck 12 in a similar fashion, wherein integrally molded ribs or flanges 100, 101, 102, 103, 104, 105, and their respective integrally molded opposed mating flanges 110, 111, 112, 113, 114, and 115 are heated to a melted state and then pressed together via the hot plate welding process in order to form pallet assembly 10. Note that the welds according to the teachings of the process should be cooled before pallet assembly 10 may achieve its optimum physical properties, including strength and load-bearing characteristics.

Focus is now directed to the method of assembling pallet assembly 10 according to the present invention. The preferred manufacturing assembly process

is by the hot plate welding process which is best illustrated in Figure 16 of the drawings. As indicated above, however, any suitable fastening means may be used such as, for example, infrared radiation, epoxy, etc. The hot plate welding process may be characterized as either contact hot plate welding or non-contact hot plate welding. This process should provide weld strength properties and produce seals between the mating (welded) components as strong as those of the parent polymer. According to the present invention, the weld surfaces, shown as ribs 60-67, 70-77, 80-87, 90-97, 100-105 and 110-115, are either placed in contact (in the contact hot plate welding process) or closely approach (in the non-contact variation) a heated platen 126 (preferably formed of steel) or similar tool in order to create a molten or plasticized region on the aforementioned ribs. Platen 126 is then moved out of the way and the plasticized regions are then pressed together to form the weld.

More particularly, in practice, the process is operated on a hot plate welding machine (known in the art) in which the corresponding pallet members which are to be welded together are clamped in holders 122 and 124. Platen 126 of welding machine, which is heated to a predetermined desirable temperature, advances between the separated mating parts (for example top deck 12 and bottom deck 14), whereupon the weld planes of the pallet members to be welded are either pressed against platen 126 (contact version using conducted heat) or are moved closely to it (non-contact version using radiant heat.) The choice of which method to use is dependant on many factors including the properties of the materials to be welded; cycle times required; size and design of the component; accuracy and repeatability of the welding machine; and use of the welded component.

In the contact hot plate welding process, heat is conducted by way of physical contact of the parts to be welded with heated platen 126. Further, the surface of each mating pallet member is plasticized or melted until contact is complete (referred to in the art as "matching"). At this point, further platen 126 movement is often halted, and heating is continued, in order to create a deeper (to a predetermined depth), and relatively more molten, plasticized zone in which material is displaced. In the non-contact process, radiant heat is applied to the parts

to be welded which is generated by holding the parts to be welded very close to the heated platen (target plates) and allowing them to heat over time.

For either version, after heating is complete and the surface melting has reached a predetermined melt depth, the parts are retracted from platen 126. Platen 126 is then moved out of the way, whereupon the adjoining pallet members (for example, top deck 12 and bottom deck 14) are forged together and held until the polymer of the plasticized pallet member surfaces cools. Mechanical or microprocessor-controlled stops may be used to control the amount of material displacement of the pallet polymer from the weld zone, particularly during the heating phase. Of course, as previously stated, the process disclosed herein is applicable to join top deck members 38 and 40, and bottom deck members 42 and 44.

If polymers between adjoining pallet members are compatible, the hot plate welding process is capable of welding dissimilar thermoplastics with the use of two platens which compensate for the different polymer melting or softening points. Hot plate welding is preferably used with standard unfilled polymers and is preferably used in this manner according to pallet assembly 10 of the present invention. However, hot plate welding may be used to assemble pallet assembly 10 with filled polymers, provided that the filler material allows the polymer to interdiffuse upon forging.

Weld times to form pallet assembly 10 may vary with the volume of polymer to be fused and the thermal conductivity of the respective pallet member. Accordingly, welding times for pallet assembly 10 may fall in the range from 5 to 60 seconds, although the mass of pallet members that are to be plasticized and the corresponding cooling rates will govern cycle times. The size of pallet assembly 10 that may be hot plate welded according to the present invention is limited only by the practical size of holding fixtures 122 and 124 and platen 126 of welding machine, and also of the mechanics of the removal of the welded assembly or subassembly from the weld zone and moving pallet assembly 10 components for forging them together.

Each of the contact and non-contact methods have their advantages, including: In the non-contact method, no special coating on platen 126 is required for material release, no residue builds-up on platen 126, there is no loss of weld edge material against heated platen 126 and finished parts have consistent weld characteristics. Whereas, the advantages of contact heating are a quicker cycle time, lower temperature required for platen 126, the method is more tolerant of larger design components, such as the pallet member disclosed herein, and also more tolerant of less dimensionally consistent components.

As shown in Figure 16a, the hot plate welder has part holding fixtures 122 and 124 attached thereto. The parts to be welded, for example and not limitation, top deck 12 and lower deck 14 are secured to their respective holding fixture 122 and 124. With reference to Figure 16b, platen 126 extends into and is inserted between pallet members 12 and 14 which are to be welded. Holding fixtures 122 and 124 move toward each other and toward platen 126. If contact welding is desired, as shown in Figure 16c, holding fixtures 122 and 124 approach platen 126 until the surfaces of decks 12 and 14 which are to be welded (surfaces 35 and 37.)

If non-contact welding of pallet assembly 10 is desired, then Figure 16c is disregarded and surfaces 35 and 37 of decks 12 and 14 do not contact platen 126. As shown in Figure 16d, after a predetermined period of time, holding fixtures 122 and 124 begin to separate and platen 126 is withdrawn from between fixtures 122 and 124. With reference to Figure 16e, fixtures 122 and 124 again move toward each other to a weld position, so that the mating surfaces of top deck 12 and bottom deck 14 are touching. Top deck 12 and bottom deck 14 are held at this final weld position for a predetermined period of time until the weld material is stable and allowed to cool. Finally, with reference to Figure 16f, fixtures 122 and 124 are separated to their part loading position and welded pallet assembly 10 is held to one of the fixtures (shown in Figure 16f as fixture 124) for unloading. The part is then removed from the welding machine.

Welding pallet assembly 10 as described herein provides a high strength weld suitable for parts operating under pressure. The joint parting lines 20, 52 and 54 are relatively inconspicuous. Further, no other attachment methods, such as adhesives, solvents, mechanical fasteners such as nails or staples, are required. Also, complex shapes such as top deck 12 and bottom deck 14 can be welded since there is no relative motion required in the welding process.

Another assembly process known as infrared radiation may also be used as a non-contact alternative to hot plate welding for use in forming and assembling pallet assembly 10 according to the present invention. In such a process, the infrared radiation is often supplied by high intensity, quartz heat lamps which produce radiation having wavelengths of around one micron. As with hot plate welding, when this radiation is applied to planar surfaces 35, 37, 46, 48, 50, 51 and of assembly 10, plasticizing occurs. In one application, radiation source, such as heat lamps, are removed after melting has occurred and the parts are forged together just as with the platen in hot plate welding. Infrared welding tends to melt the zone relatively quickly. Hot plate welding uses conduction to create the necessary plasticized zone. Of course, as with any other process, the depth of penetration of the plasticization depends on many factors and it varies strongly with only minor changes in polymer formulation.

Focus is now directed to the load-bearing properties of pallet 10. In a racking scenario, pallet 10 is supported from below on two opposing edges and loaded from above on upper surface 26 of top deck 12. Pallet 10 should support this load with a minimum of deflection. According to standard beam formulas known in the art, it is recognized that deflection increases as the load or the span distance increases, and decreases as the material modulus (E) or section moment of inertia (I) increases. Since the load and the span are defined for a given application, the variables used to minimize deflection are the material and the section design.

Generally, as the E value increases for a given material, the impact strength decreases. There exist engineered materials that may solve these problems but they are too expensive for wide spread use. The most common method is to use

a commodity resin such as polyethylene or polypropylene and add a filler to stiffen the resin. However, fillers add weight and reduce impact strength for a given material as well as impact the recyclability in some cases, and add cost. Preferably, a pallet would use a commodity resin because of cost, weight, and impact strength.

5 Accordingly, optimizing the design of the pallet is the preferred method to achieve improved pallet performance.

As previously noted, for a given section geometry the highest I value is for a solid section. For instance, in pallet assembly 10, the stiffest top deck 12 design is one that is solid plastic, but this is impractical because of weight and cost. 10 Most designs attempt to overcome this by using ribbed sections instead of solid sections to minimize the loss of I and reduce the weight to an acceptable level. Another method is to use foaming agents along with the ribs to minimize the weight of the ribs and improve the I value. Both methods have a limit to their effectiveness. Namely, ribs are not the ideal geometry to maximize the I value and while foaming 15 improves this slightly, it also reduces the impact strength of the material.

Generally, for a given section the material closest to the neutral axis or center has the least affect on I and the material farthest away has the greatest effect. In other words, a hollow or I-beam section is stiffer than a rectangular section of equal height and area. Thus, pallet 10 design according to the present 20 invention defines hollow or boxed sections throughout the pallet and in a continuous manner. Conventional injection molding techniques make this virtually impossible. Therefore, using a 3-step fastening operation (preferably welding) results in box beam pallet 10 formed from four individual component members, 38, 40, 42, 44, which are preferably injection molded.

25 In summary, the first or top member 38 preferably includes a substantially flat top surface with ribs protruding in a downward direction. The second or mid-top member 40 has a substantially flat bottom surface with ribs extending in an upward direction and partial support columns extending down from this surface. The ribs on both these parts are aligned so they can be welded together 30 by plasticizing their mating surfaces preferably via a hot-plate welding operation to

form a box beam top deck. The third or mid-bottom member 44 has a substantially flat upper surface with ribs extending down and partial columns extending up. The fourth or bottom member 42 has a substantially flat bottom surface with ribs extending up. Again, the ribs on both parts are aligned so they can be welded together in a second hot plate welding operation to form box beam bottom deck 14. Lastly, the box beam top deck and box beam bottom deck are welded together at the columns (16, 18, 19, 32) that also align, resulting in a pallet where every section is a box beam. Note that the order of the plasticizing procedure is provided for illustrative purposes only, and of course, such steps may be performed in any feasible order.

Of course, it is also contemplated according to the present invention that the box beam sections may be formed by one planar surface being ribbed area defining a U area (for example in Figure 14, between top member 38 and mid-top member 40, ribs 63, 64 and surface 9 define a U-area or a partial box-beam section) while the mating planar surface 48, instead of including ribs, would form a flat surface, thereby creating a fourth wall which closes out the U area and defines a box section. Again, of course, this would apply to all surfaces to be hot plate welded according to the present invention.

In the preferred embodiment, each boxed section has a plurality of perforations or apertures 22,24 in the top and bottom decks to allow for cleaning and drainage. These perforations may easily be eliminated to create true boxed sections. More particularly, apertures 22 in top member 38, apertures 57 in mid-top member 40, apertures 24 in bottom member 42, and apertures 59 in mid-bottom member 44 are tapered so that they increasingly get larger from top surface 26 to bottom surface 28, or from washing side to non-washing side, in order to provide for ease of water drainage through pallet 10 (see Figures 5-6.)

While other methods of forming plastic parts exist, these methods are not capable of forming the present design. For example, blow molding is limited to hollow sections and cannot create cross ribbing within the hollow sections to form the smaller boxed sections defined by the ribs of the present invention which assist

in achieving the desired stiffness. Extrusion is also limited in that its hollow sections and internal ribs must be oriented in the same direction for a given component. Extrusions also have open ends that must be sealed in a secondary operation to create a "clean" pallet, and therefore is labor intensive and costly to produce.

5 It is noted that the design according to the present invention preferably includes full and continuous box-beam sections across the entire pallet 10, i.e. every section being fully boxed in: top deck 12, bottom deck 14 and columns 16, 18, 19, 32. The remarks and disclosure made herein with regard to material modulus (E), moment of inertia (I), section geometry, beam formulas, and stiffness, generally
10 apply to all embodiments and features disclosed in this application.

 With focus now on Figures 17-27, also disclosed according to the teachings of the present invention is a top frame 210 for a pallet. A top frame is typically used in connection with the mass shipping of objects, such as empty bottles (see Figure 18). The top frame is used to help stabilize the top of a shipment of
15 objects in conjunction with a pallet at the bottom of the shipment. Top frame 210 is preferably and generally symmetrical about each centerline, and is formed of thermoplastic or other polymeric material and is preferably, but not necessarily, formed of injection molded components.

 Referring to Figures 17-27, shown therein is a top frame assembly 210
20 according to the present invention. The box beam design according disclosed herein for pallet 10 is also applicable to top frame assembly 210. Figure 17 illustrates a perspective view of top frame assembly 210. Top frame assembly 210 includes a top (first) member 212 and a bottom (second) member 214 (see the exploded perspective views of Figures 25 and 26). Figure 18 shows top frame assembly 210 in
25 operation. As illustrated therein, a pallet such as pallet 10 according to the present invention, has loaded thereon a plurality of layers of objects for transport and storage. Such objects are shown in Figure 18 as a plurality of empty bottles 216, but of-course may be any-of various objects which may be transported by and stored on pallet and to which the teachings according to the present invention would apply.

A first layer of bottles 216 is loaded on pallet 210. Typically, a planar member 218 is positioned on the upper surface of bottles 216. Planar member 218 may be referred to as a slip sheet in the art, and is typically formed of cardboard or fiberboard. As illustrated, another layer of bottles 216 may be disposed on top of planar member 218, and then another planar member 218 is positioned on top of that layer of bottles 216. This procedure is repeated for as many layers as is practical and desired, for example the eight layers of bottles shown in Figure 18. After the final planar member is positioned, top frame 210 is positioned on top of the planar member so that the product is sandwiched. Pallet 10 and top frame 210, with the objects disposed therebetween, are strapped together via straps 220. As shown in Figures 17, 18, 19, and 26, top frame 210 preferably also includes a series of recesses 221 around its perimeter in which straps 220 are positioned so that they do not move or shift easily during shipment. Subsequently, the resulting packaging (as shown in Figure 18) is typically covered and protected, such as by applying a shrink plastic wrap.

Figure 19 illustrates a top plan view of top frame 210. As shown therein, top frame 210 includes four openings 244 defined by outer rail 246 and cross rails 248, 249. Openings 244 assist in lowering the weight of top frame 210 while the disclosed box-beam sections provide the desired strength and rigidity to top frame 210, similar to the properties disclosed with respect to pallet 10. Figure 20 illustrates a front side elevational view of top frame 210, particularly showing side 236. Figure 21 shows a side elevational view of top frame 210, particularly illustrating side 221. Figure 22 illustrates a cross-sectional view of section line 22-22 in Figure 19. Figure 23 illustrates another cross-sectional view of section line 23-23 in Figure 19. Figure 24 illustrates a bottom plan view of first top frame member 212.

Top frame 210 includes a first pair of opposing edges 220, 222 and a second pair of opposing edges 224, 226. Top frame edge 220 is defined by first top frame member and second top frame member edges 228 and 230, respectively; top frame edge 222 by member edges 232 and 234, respectively; top frame edge 224

by member edges 236 and 238, respectively; and top frame edge 226 by member edges 240 and 242, respectively.

According to the present invention, first top frame member 212 and second top frame member 214 are fastened to each other in a method substantially similar to that disclosed herein in association with fastening or welding pallet 10, pallet top deck 12, and pallet bottom deck 14. Referring to Figures 25, 26 and 27, for example, first top frame member 212 includes a substantially flat top surface 213 and a plurality of ribs, for example ribs 250, 251, 252, 253, 254, 255, 256, 257, 258, and 259 (250-259) protruding in a downward direction. Second top frame member 214 has a substantially flat bottom surface 217 with a plurality of ribs 260, 261, 262, 263, 264, 265, 266, 267, 268, and 269, extending in an upward direction and which correspond to and mate with those ribs 250-259, respectively, of first top frame member 212. Figure 27 illustrates a cross-section of top frame 210 taken along line 27-27 of Figure 19. Figure 27 illustrates that fastening together, or welding, each of the above respective pairs of ribs 250-259 and 260-269 define box-beam section walls 270, 271, 272, 273, 274, 275, 276, 277, 278, 279 of top frame 210.

Likewise, for example, ribs 280, 281, 282, 283, 284, 285, 286, 287, 288, 289 of first top frame member correspond and mate with ribs 290, 291, 292, 293, 294, 295, 296, 297, 298, 299, respectively, of second top frame member. The corresponding ribs on both members 212, 214 are aligned so they preferably are welded together by plasticizing their mating surfaces preferably via a hot-plate welding operation to form box-beam top frame assembly 210, resulting in a top frame where every section is a box beam. Note that the order of the plasticizing procedure is provided for illustrative purposes only, and of course, such steps may be performed in any feasible order. Also, as with pallet 10, the plasticizing process for the top frame may also be accomplished by infrared radiation or another process designed to provide the desired properties of top frame 210.

First top frame member 212 and second top frame member 214 have corresponding planar surfaces 211, 215 which when mated together and fastened,

define parting line 219. Thus planar surfaces 211 and 215 include the corresponding upper or lower edges of ribs 250-259, 260-269, 280-289, and 290-299.

Top frame 210 thus provides greater load stability which allows the objects 216 to be stacked higher and with greater stability. Further, with top frame 210 positioned and secured on top of the stack, it is contemplated that another pallet, such as pallet 10, may be stacked on top of top frame 210. The box-beam sections extending across top frame 210 also provide improved stiffness and strength to the part and minimize any bowing or flexing of the part, and also to minimize or prevent any deformation that would result from applying straps 220 to a wood top frame. Top frame 210 also includes a recess 223 for receiving a grommet (not shown) therein for providing skid or slip resistance when stacking top frames.

Figure 28a illustrates a perspective view of a second embodiment of a top frame 210' according to the present invention. Similar features to those disclosed in the first top frame embodiment are assigned a like reference numeral with a prime (') designation. As further illustrated in the exploded views of Figures 28b and 28c, top frame 210' includes an outer rail 246' and has a single opening 244'. Top frame 210' also includes recesses 221' for receiving straps 220 therein. Accordingly, with reference to the first and second top frame embodiments 210 and 210', it is contemplated that the top frame according to the present invention may have various designs without departing from the teachings according to the present invention. Thus, top frame 210' includes box beam sections around and between components first top frame member 212' and second top frame member 214' which define rail 246' as illustrated in Figures 28b and 28c. In the same manner as disclosed with respect to top frame 210 above, top frame 210' also includes mating planar surfaces 211' and 215' which when fastened according to the teachings of the present invention define box beam sections therein as well as the parting line 219' between first top frame member 212' and second top frame member 214'. Therefore, this alternative design of top frame assembly 210' has the desired stiffness and properties as described in relation to pallet 10 and top frame 210 above.

Referring now to Figures 29-34, an alternative box-beam design is also disclosed according to the present invention and in association with Figures 29-34. While the box-beam design according to the present invention and shown in Figures 29-34 provides many advantages not heretofore found in the art, the embodiment shown and described in association with Figures 29-34, relative to the above embodiments, may not completely achieve the properties and characteristics of pallet 10 above, because many areas which may limit deflection may not have a boxed section in this alternative box beam section design.

In a racking scenario, the plastic pallet 310 (which is configured to receive a pallet jack from any side), shown in Figure 29, is supported from below on two opposing edges 312, 314, and loaded on the top deck portion 316. The pallet must support this load with a minimum of deflection. The top deck portion 316 is supported by a plurality of support columns 318 extending from the top deck portion 316 and attached to the support rails 320, which form the bottom deck 319. The support rails 320 are generally relatively weak structural portions of the pallet because they are thin in vertical cross-section and are supported only at opposing ends by the columns 318. Accordingly, the support rails 320 tend to deflect when the pallet is loaded.

As mentioned above, deflection decreases as the section moment of inertia (I) increases. For a pallet, the easiest method to increase stiffness is to increase height. However, in practice there is a maximum allowable height for pallets, and existing pallets are generally designed at this maximum value. Accordingly, the only alternative is to maximize the moment of inertia for the pallet, and particularly for each pallet component, namely the top deck 316, bottom deck and support rails 320.

Therefore, the object of the design is to create hollow or boxed sections everywhere possible. Conventional injection molding techniques make this almost impossible to create, but by using a secondary operation, it is possible to form a boxed top deck 316 and bottom deck 319.

A pallet in accordance with the present invention includes the top deck portion 316, which is injection molded conventionally and consists of a flat upper surface 322 with a series of ribs 324 protruding from the upper surface 322 as shown in Figure 30. The top deck portion 316 includes a plurality of pockets 326 for receiving the support columns 318. A plurality of plastic sheet strips 328 are sonically welded to the ribs 324 to form a plurality of substantially rectangular hollow boxed sections between the pockets 326 within the top deck 316 (as described later with reference to Figure 32). Alternatively, other attachment methods such as vibratory welding, hot plate welding, adhesive etc. may be used for attachment of the plastic sheet strips 328.

The bottom deck 319 is constructed similarly but has the support columns 318 integrally molded therewith. Ribs 330 protrude downwardly from the sheet portions 332 of the support rails 320, and a plurality of plastic sheet strips 334 are welded to the ends of the ribs 330 to form a plurality of boxed cross-sections along the length of the rails 320 between the columns 318. The top and bottom decks 316, 319 may be joined permanently by welding, or can be snapped together as commonly known in the art.

The method described above is preferably used to stiffen conventional ribbed pallet designs. The small sheets of plastic 334 are welded into critical deflection areas of the existing pallets for stiffening. Also, new pallets could be designed to accept the sheets for applications that require racking, and would eliminate the sheets for lighter, lower cost applications. For example, the ribs 330 may be recessed in order to receive the sheets 334 in a position flush with the bottom surface of the support rails 320.

The method described above is particularly applicable for use in pallets such as that shown in Figure 29 which has a very thin top deck 316 and bottom deck 319 to allow four-way entry of pallet jacks. The method described may be used to maximize the moment of inertia of each deck member.

Referring to Figure 32, an alternative embodiment of the invention is shown. Similar to the embodiment shown in Figure 29, the bottom deck rails 340 include a sheet portion 342 with a plurality of vertical ribs 344 extending therefrom. The plastic sheet strips 346 are welded to the ribs 344 to form the plurality of substantially rectangular hollow vertical cross-sections 348 along the length of the support rails 340. Of course, numerous ribs 344 could be added to create numerous rectangular cross-sections for further improved structural integrity.

The pallet shown in Figure 32 differs from the earlier embodiment described with reference to the Figures 29-31 in that a large sheet 350 is welded to the ribs 352 across the breadth of the upper deck 354 for improved structural integrity of the upper deck 354.

It is contemplated that good results could be achieved even by only welding the peripheral ribs to the plastic sheet strips. It is further contemplated that the plastic sheet strips need not be welded, but could be affixed in any manner, such as adhesive, etc. It is also contemplated that the sheet strips need not be plastic.

Referring to Figures 33 and 34, another alternative embodiment of the invention is shown. In this embodiment, the pallet 410 includes a thin top deck 416 connected to a thin bottom deck 419 by nine support columns 418. The bottom deck 419 includes a plurality of support rails 420 which extend between the columns 418. Each support rail 420 includes a sheet portion 422. Because each support rail 420 forms a relatively weak structural portion of the pallet 410, an extruded plastic rectangular tube 427 is welded against each respective sheet portion 422 to add stiffness to each support rail by forming substantially rectangular vertical cross-sections along the length of each support rail 420. Similarly, the top deck 416 includes open channels 428 adjacent the top sheet 430, and an extruded plastic rectangular tube 431 is welded within each channel 428 against the top sheet 430 between the columns 418 to form substantially rectangular vertical cross-sections along the length of each channel 428 between the columns 418 for improved stiffness. In this configuration, the rectangular tubes 427,431 may be inexpensively

extruded, and add substantial structural integrity to the pallet 410 without limiting the pallet's ability to receive pallet jacks from any side thereof.

5 While embodiments of the invention have been illustrated and described, it is not intended that these embodiments illustrate and describe all possible forms of the invention. Rather, the words used in the specification are words of description rather than limitation, and it is understood that various changes may be made without departing from the spirit and scope of the invention.

WHAT IS CLAIMED IS:

- 1 1. A plastic pallet assembly comprising:
2 a top deck having a plurality of upper box beam sections
3 disposed therein, and having a first opposing surface having a plurality of first
4 column portions projecting downwardly therefrom; and
5 a bottom deck having a plurality of lower box beam sections
6 disposed therein, and having a second opposing surface having a plurality of second
7 column portions projecting upwardly therefrom, the plurality of second column
8 portions corresponding to and securely mating with the plurality of first column
9 portions to define a plurality of box beam cross-sections between the top deck and
10 bottom deck for providing strength to the pallet assembly.
- 1 2. The plastic pallet assembly of claim 1 wherein the top deck
2 includes a top member and a mid-top member each having mating corresponding
3 fastened flange portions defining the plurality of upper box beam sections.
- 1 3. The plastic pallet assembly of claim 1 wherein the bottom deck
2 includes a bottom member and a mid-bottom member each having mating
3 corresponding fastened flange portions defining the plurality of lower box beam
4 sections.
- 1 4. A pallet assembly comprising:
2 a top deck formed of plastic and having a first opposing surface
3 having a plurality of first flanged portions projecting downwardly therefrom; and
4 a bottom deck portion formed of plastic and having a second opposing
5 surface having a plurality of second flanged portions projecting upwardly therefrom,
6 the plurality of second flanged portions corresponding to and securely mating with
7 the plurality of first flanged portions to define a plurality of box beam cross-sections
8 between the top deck and bottom deck portions for providing strength to the pallet
9 assembly.

1 5. The pallet assembly of claim 4 wherein the top deck portion
2 includes a top member and a mid-top member having corresponding mating flanged
3 surfaces which are securely mated to each other to define a plurality of upper box
4 beam sections, the mid-top member having the first opposing surface opposite its
5 respective one of the corresponding mating flanged surfaces.

1 6. The pallet assembly of claim 4 wherein the bottom deck
2 portion includes a bottom member and a mid-bottom member having corresponding
3 mating flanged surfaces which are securely mated to each other to define a plurality
4 of lower box beam sections, the mid-bottom member having the second opposing
5 surface opposite its corresponding mating flange surfaces.

1 7. The pallet assembly of claim 4, wherein the top deck portion
2 has a substantially planar upper surface upon which a plurality of objects are capable
3 of resting.

1 8. A pallet assembly comprising:
2 a first pallet portion formed of plastic and having a first opposed
3 surface having a plurality of first spacer portions projecting downwardly therefrom
4 having a first matching surface; and
5 a second pallet portion formed of plastic and having a second opposed
6 surface having a plurality of second spacer portions projecting upwardly therefrom
7 having a second matching surface, the plurality of first and second matching surface
8 heated to a plasticized state, compressed together, and cooled to define a plurality
9 of columns for spacing apart the first pallet portion and the second pallet portion,
10 each column having a box beam cross-sections for providing strength to the pallet
11 assembly.

1 9. The pallet assembly of claim 8 wherein the first pallet portion
2 includes a first outer member and a first inner member having opposing surfaces
3 which are securely attached to each other by heating the opposing surfaces to a
4 plasticized state, compressing them together, and cooling them.

1 10. The pallet assembly of claim 9 wherein the first outer member
2 has a substantially planar first outer surface for supporting and transporting an object
3 thereupon.

1 11. The pallet assembly of claim 8 wherein the second pallet
2 portion includes a second outer member and a second inner member having opposing
3 surfaces which are securely mounted to each other by heating the opposing surfaces
4 to a plasticized state, compressing them together, and cooling them.

1 12. A pallet assembly comprising:
2 a first pallet portion formed of plastic and including a top member
3 and a top intermediate member, each having a one of a first pair of substantially
4 planar surfaces spaced apart from the other and each further having a one of a first
5 pair of mating surfaces which are heat welded together to integrally define the first
6 pallet portion; and
7 a second pallet portion formed of plastic and including a bottom
8 member and a bottom intermediate member, each having a one of a second pair of
9 substantially planar surfaces spaced apart from the other and each further having a
10 one of a second pair of mating surfaces which are heat welded together to integrally
11 define the second pallet portion,
12 wherein the first intermediate member of the first pallet portion and
13 the second intermediate member of the second pallet portion have corresponding
14 opposed mating edges which are heat welded to each other to integrally define the
15 pallet assembly.

1 13. A pallet assembly formed substantially of plastic comprising:
2 a first outer member and a first intermediate member spaced apart
3 from each other by a first pair of opposed mating surfaces extending therebetween
4 which are integrally mounted to each other to define a first pallet portion; and
5 a second outer member and a second intermediate member spaced
6 apart from each other by a second pair of opposed mating surfaces extending
7 therebetween which are integrally mounted to each other to define a second pallet

8 portion, the second intermediate member being oriented adjacent the first
9 intermediate member,
10 wherein the first intermediate member and the second intermediate
11 member have corresponding mounting edges projecting therefrom which are
12 integrally mounted to each other to integrally define the pallet assembly.

1 14. The pallet assembly of claim 13 wherein the first outer member
2 includes a lower surface with edges projecting therefrom defining a one of the first
3 pair of opposed mating surfaces, and the first intermediate member having an upper
4 surface with corresponding edges projecting therefrom defining an other of the first
5 pair of opposed mating surfaces, and
6 wherein the second outer member includes an upper surface with
7 edges projecting therefrom defining a one of the second pair of opposed mating
8 surfaces, and the second intermediate member having a lower surface with
9 corresponding edges projecting therefrom defining an other of the second pair of
10 opposed mating surfaces.

1 15. A pallet assembly for storing and transporting objects thereon,
2 comprising:
3 a first member having a substantially planar first upper surface upon
4 which the objects are placed, and a first lower surface;
5 a second member having a second upper surface and a second lower
6 surface, the second upper surface securely mounted to the first lower surface;
7 a third member having a third upper surface and a third lower surface,
8 the third upper surface and the second lower surface having corresponding flanged
9 surfaces securely mounted to each other to form a plurality of columns having box
10 beam cross-sections; and
11 a fourth member having a fourth upper surface for mating with the
12 third lower surface and a substantially planar fourth lower surface, the fourth upper
13 surface securely mounted to the third lower surface.

1 16. The pallet assembly of claim 15 wherein the second upper
2 surface and first lower surface are securely mounted by introducing heat

3 therebetween, plasticizing each surface, compressing the surfaces together, and
4 allowing them to cool.

1 17. The pallet assembly of claim 15 wherein the fourth upper
2 surface and third lower surface are securely mounted by introducing heat
3 therebetween, plasticizing each surface, compressing the surfaces together, and
4 allowing them to cool.

1 18. A method of forming a pallet comprising:
2 providing first and second pallet portions, each having corresponding
3 mating flanged surfaces;
4 introducing heat to the corresponding mating flanged surfaces to melt
5 the mating flanged surfaces thereby forming plasticized surfaces;
6 pressing the plasticized surfaces together; and
7 cooling the plasticized surfaces forming a welded joint therebetween
8 defining a plurality of box sections by the mating flanged surfaces.

1 19. The method of claim 18 wherein providing a first and second
2 pallet portions includes mounting and aligning them in a holding fixture.

1 20. The method of claim 19, further comprising opening the
2 holding fixture and removing the welded pallet assembly.

1 21. The method of claim 18, wherein introducing heat to the
2 corresponding mating flanged surfaces includes introducing a heated platen
3 therebetween.

1 22. The method of claim 18 further comprising:
2 retracting the heated platen from between the corresponding mating
3 flanged surfaces.

1 23. The method of claim 18, further comprising heating the mating
2 flanged surfaces under pressure by contacting the heated platen to the mating flanged
3 surfaces for melting the same.

1 24. A method of forming a plastic pallet assembly, comprising:
2 providing a top deck portion having a plurality of upper box beam
3 sections disposed therein and having a first opposing surface with a plurality of first
4 column portions projecting downwardly therefrom;
5 providing a bottom deck portion having a plurality of lower box beam
6 sections disposed therein and having a second opposing surface with a plurality of
7 second column portions projecting upwardly therefrom; and
8 securely attaching the plurality of second column portions to
9 corresponding plurality of first column portions to define a plurality of box beam
10 cross-sections between the top deck and bottom deck for providing strength to the
11 pallet assembly.

1 25. A top frame assembly adapted for use with a pallet, wherein the
2 top frame assembly and the pallet have at least one layer of objects positioned
3 therebetween, the top frame assembly comprising:
4 first and second top frame members, one of the first and second top
5 frame members having a plurality of ribs projecting toward the other of the first and
6 second top frame members, the other of the first and second top frame members
7 having a mating surface for mating with the plurality of ribs, the plurality of ribs
8 and the mating surface are being fastened to each other to form a plurality of
9 complete box beam sections between the first top frame member and the second top
10 frame member.

1 26. A top frame adapted for use with a pallet having at least one layer
2 of objects to be transported positioned thereon, the top frame comprising:
3 a first top frame member having a plurality of downstanding ribs
4 extending therefrom defining a first plurality of partial box-beam sections thereon;
5 and

6 a second top frame member having a corresponding plurality of
7 upstanding ribs extending therefrom defining partial box-beam sections thereon
8 defining a second plurality of partial box-beam sections thereon, the downstanding
9 ribs and the upstanding ribs are attached to each other to form a plurality of complete
10 box beam sections between the first top frame member and the second top frame
11 member.

1 27. The top frame of claim 26 wherein the downstanding ribs and
2 the upstanding ribs are attached by plasticizing and welding to each other.

1 28. The top frame of claim 26 wherein the plurality of complete
2 box-beam sections extend between opposing edges of the top frame.

1 29. A method of forming a top frame for use with a pallet,
2 comprising:
3 providing first and second top frame members, at least one of the first
4 and second top frame members having a ribbed surface, and the other of the first and
5 second top frame members having a corresponding mating surface for mating with
6 the ribbed surface;
7 introducing heat to the corresponding ribbed and mating surfaces to
8 melt the mating ribbed surfaces thereby forming plasticized surfaces;
9 pressing the plasticized surfaces together; and
10 cooling the plasticized surfaces forming a welded joint therebetween
11 defining a plurality of box sections by the mating ribbed surfaces.

1 30. The method of claim 29 wherein providing a first and second
2 top frame portions includes mounting and aligning them in a holding fixture.

1 31. The method of claim 30, further comprising opening the
2 holding fixture and removing the welded first and second top frame members.

1 32. The method of claim 29, wherein introducing heat to the
2 ribbed and mating surfaces includes introducing a heated platen therebetween.

1 33. The method of claim 29 further comprising retracting
2 the heated platen from between the corresponding ribbed and mating surfaces.

1 34. The method of claim 29, further comprising heating the ribbed
2 and mating surfaces under pressure by contacting the heated platen to the mating
3 ribbed surfaces for melting the same.

1 35. A method of forming a top frame assembly, comprising:
2 providing a first top frame member having a plurality of upper box
3 beam sections disposed therein and having a first opposing surface;
4 providing a second top frame member having a plurality of lower box
5 beam sections disposed therein; and
6 securely attaching the plurality of second column portions to
7 corresponding plurality of first column portions to define a plurality of box beam
8 cross-sections between the top deck and bottom deck for providing strength to the top
9 frame assembly.

1 36. A method of reinforcing a plastic pallet having a plurality of
2 relatively weak structural portions each including a sheet portion with a plurality of
3 vertical ribs extending therefrom, wherein the sheet portion and ribs cooperate to
4 form a plurality of U-shaped vertical cross-sections along the length of the pallet and
5 each U-shaped cross-section having an open end, the method comprising:
6 affixing a plurality of planar sheet strips to the vertical ribs in said
7 plurality of relatively weak structural portions, respectively, to fully enclose the open
8 ends of said U-shaped cross-sections to form a plurality of rectangular hollow
9 vertical cross-sections along the length of the relatively weak structural portions for
10 improved stiffness.

11 37. The method of claim 36 wherein said step of affixing a
12 plurality of sheet strips comprises welding a plurality of plastic sheet strips.

1 38. The method of claim 37 wherein said welding step comprises
2 sonic welding.

1 39. The method of claim 36, wherein the plastic pallet comprises
2 a commodity resin material having a flexural modulus of less than 200,000 psi.

1 40. A method of reinforcing a plastic pallet having a top deck
2 portion, a plurality of support columns extending from the top deck portion and a
3 plurality of support rails connected to the support columns, wherein the support rails
4 include a sheet portion with a plurality of vertical ribs extending therefrom, and
5 wherein the sheet portion and ribs cooperate to form a plurality of U-shaped vertical
6 cross-sections along the length of the pallet and each U-shaped cross-section having
7 an open end, the method comprising:

8 welding a plurality of planar plastic sheets to the vertical ribs between
9 the support columns, respectively, to fully enclose the open ends of said U-shaped
10 cross-sections to form a plurality of rectangular hollow vertical cross-sections along
11 the length of the support rails for improved stiffness.

1 41. The method of claim 40, wherein the top deck portion includes
2 a top wall with a plurality of vertical ribs extending therefrom, the method further
3 comprising welding at least one plastic sheet to the vertical ribs on the top deck
4 portion to form a plurality of substantially rectangular vertical cross-sections along
5 the length of the top deck portion for improved stiffness.

1 42. The method of claim 40, wherein said step of welding a
2 plurality of plastic sheets comprises sonic welding a plurality of plastic sheets.

1 43. The method of claim 40, wherein the plastic pallet comprises
2 a commodity resin material having a flexural modulus of less than 200,000 psi.

1 44. A method of reinforcing a plastic pallet having a thin top deck
2 connected to a thin bottom deck by nine support columns, wherein the thin bottom

3 deck comprises a plurality of support rails extending between the support columns,
4 the method comprising:

5 welding a plastic reinforcement member to each of the support rails,
6 such that each reinforcement member and the respective support rail cooperate to
7 form rectangular vertical cross-sections along the length of the support rail for
8 improved stiffness;

9 wherein each said support rail comprises a sheet portion, and each said
10 plastic reinforcement member comprises an extruded rectangular tube which is
11 welded to the respective sheet portion to form said substantially rectangular vertical
12 cross-sections.

1 45. The method of claim 44, wherein said plastic pallet comprises
2 a commodity resin material having a flexural modulus of less than 200,000 psi.




Fig. 1

Fig. 2





Fig. 3






Fig. 4




Fig. 5




Fig. 6

7/29

Fig. 7






Fig. 8



9/29

*Fig. 9*

10/29





Fig. 10


11/29

Fig. 11



12/29

Fig. 12



13/29




Fig. 13




Fig. 14





Fig. 15



17/29

Fig. 17







Fig. 19

18/29

*Fig. 18*






Fig. 25




Fig. 26




Fig. 27

Fig. 28a

23/29




Fig. 28b




Fig. 28c




Fig. 29




Fig. 30




Fig. 31




Fig. 32




Fig. 33




Fig. 34

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US99/14399

A. CLASSIFICATION OF SUBJECT MATTER

IPC(6) :B65D 19/00

US CL :108/57.25

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 108/57.25, 57.26, 57.27, 901, 902

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X ----	US 3,467,032 A (ROWLANDS ET AL) 16 September 1969 (16/09/69), see entire document.	18-23 -----
Y		1-17, 24-45N
Y	US 3,667,403 A (ANGELBECK, JR.) 06 June 1972 (06/06/72), see entire document.	1-17, 24-35
A	US 3,680,496 A (WESTLAKE, JR) 01 August 1972 (01/08/72), see entire document.	1-45
A	US 3,938,448 A (NISHITANI ET AL) 17 February 1976 (17/02/76), see entire document.	1-45
A	US 4,133,270 A (RAVERA) 09 January 1979 (09/01/79), see entire document.	1-45

☒ Further documents are listed in the continuation of Box C. ☐ See patent family annex.

* Special categories of cited documents:	*T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
A document defining the general state of the art which is not considered to be of particular relevance	*X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
B earlier document published on or after the international filing date	*Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	*G* document member of the same patent family
O document referring to an oral disclosure, use, exhibition or other means	
P document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search

20 SEPTEMBER 1999

Date of mailing of the international search report

21 OCT 1999

Name and mailing address of the ISA/US
Commissioner of Patents and Trademarks
Box PCT
Washington, D.C. 20231

Facsimile No. (703) 305-3230

Authorized officer
JOSE V. CHEN

Telephone No. (703) 308-2168

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US99/14399

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 5,555,820 A (SHUERT) 17 September 1996 (17/09/96), see entire document.	2, 3, 5, 6, 9-17
A	US 4,220,100 A (PALOMO ET AL) 02 September 1980 (02/09/80), see entire document.	1-45

THIS PAGE BLANK (USPTO)